



IWEISS

RIGGING EQUIPMENT

Underhung Loft Block



Stage
Rigging
Equipment
by IWEISS

The underhung loft block is solely intended for the use of mounting to the underside of a structural flange in order to direct the lift lines before they are attached to the load that is being supported or lifted.

TECHNICAL DATA

Part # WLB-1NX

- Specs**
- Underhung mounting
 - 8" diameter ASTM Class 30 grey iron or nylon sheave
 - 3/16" steel side plate
 - 3/4" steel draw bolt allows for mount direct to beams up to 3/8-3/4" thick and 4" - 9" wide
 - Idler options are two line nylon sheave with two ball bearings

Weiss Lock Block - X Lift Lines X Sheave X Idler X U

Part#	Lines	Sheave	Bearing	Capacity	Self Weight	Idler
WLB-3161N	(1) 3/16"	8" Nylon	Ball Bearing	525	10	
WLB-251NU	(1) 1/4"	8" Nylon	Ball Bearing	750	10	
WLB-251NU-2	(1) 1/4"	8" Nylon	Ball Bearing	750	11	(2) 1/4"
WLB-251NU-4	(1) 1/4"	8" Nylon	Ball Bearing	750	12	(4) 1/4"
WLB-251NU-6	(1) 1/4"	8" Nylon	Ball Bearing	750	13	(6) 1/4"
WLB-251NU-8	(1) 1/4"	8" Nylon	Ball Bearing	750	14	(8) 1/4"

